

**SPECIFICATIONS:**

**1. WIRE ROPE:**

FOR USE WITH 9/16" DIAMETER WIRE ROPE

**2. PITCH DIAMETER**

10" P.D.

**3. MATERIAL:**

CAST IRON

**4. BEARING:**

ROLLER BEARING  
SUITABLE FOR HEAVY  
DUTY APPLICATION

**5. BEARING LIFE:**

STATIC LOAD RATING:  
52,300 LBS.

BASIC DYNAMIC LOAD RATING:  
25,900 LBS.

AT 33-1/3 RPM FOR  
500 HRS MIN (L10) LIFE

**6. SHAFT BORE DIAMETER:**

3"

**7. SHAFT DIAMETER REQUIRED:**


3.0000" <sup>+0.0000</sup>/<sub>-.0010</sub>

**8. SHAFT HARDNESS:**

CASE HARDENED TO 60 R.C.

**9. SHAFT SURFACE FINISH REQUIRED:**

8  $\sqrt{\text{MAX.}}$



ELECTROLIFT, INC.  
204 SARGEANT AVE.  
CLIFTON, NJ 07013  
PH: 973-471-0204  
FAX: 973-471-2814  
www.electrolift.com

REV.	ECO#	DATE	BY:
SHEAVE PART NUMBER: M1210P4AL			
DATE: 2/27/08	SCALE: 1/3	DWG SIZE: A	DRAWN BY: DR

DRAWING NO:  
M1210P4AL-WPDF