



*ALLOW 6" CLEARANCE TO SERVICE BRAKE

CUSTOMER:

REFERENCE NO.:

ELECTROLIFT AUTHORIZED DISTRIBUTOR:

	CATALOG #			
	22-PL	-	-	-
SPEED (FPM):	15	-	-	-
LIFT (FT):	20	-	-	-
CAPACITY (LBS):	2000 LBS			
REEVING:	4 PART SINGLE			
PRIMARY VOLTAGE:	460 or 230 (3 PH. STD)			
CONTROL VOLTAGE:	115 (STD)			
HOIST WEIGHT (LBS):	350			
HP:	1-1/2			
WHEEL LOADINGS (LBS PER WHEEL PAIR):				
FULL UP		FULL DOWN		
LEFT SIDE	RIGHT SIDE	LEFT SIDE	RIGHT SIDE	
437	1913	718	1632	
HOOKBLOCK DRIFT AT FULL DOWN POSITION (IN.) (X): 3-3/4				
HOIST NOTES:				
1. LARGER CONTROL BOXES MAY NEED TO BE RELOCATED				
2. S4 TRACK = 20"				
3. S5 TRACK = 19-5/8"				
3. TRACK WIDTH EXCEEDS 5" = 20-7/8"				

ELECTROLIFT, INC.
204 SARGEANT AVE.
CLIFTON, NJ 07013
PH: 973-471-0204
FAX: 973-471-2814
www.electrolift.com

REV.	ECO#	DATE	BY:
HOIST TYPE: "A" SINGLE HOOK			
CONFIGURATION: PLAIN TROLLEY			
DATE:	SCALE:	DWG SIZE:	DRAWN BY:
6/22/04	1:12	B	AR
CATALOG NO:		DRAWING NO:	
22-PL		A-109	