


\*ALLOW 6" CLEARANCE  
TO SERVICE BRAKE

CUSTOMER:  
  
REFERENCE NO.:

ELECTROLIFT AUTHORIZED DISTRIBUTOR:

	CATALOG #			
	22-SD	-	-	-
SPEED (FPM):	15	-	-	-
LIFT (FT):	20	-	-	-
CAPACITY (LBS):	2000 LBS			
REEVING:	4 PART SINGLE			
PRIMARY VOLTAGE:	460 or 230 (3 PH. STD)			
CONTROL VOLTAGE:	115 (STD)			
HOIST WEIGHT (LBS):	350			
HP:	1-1/2			
WHEEL LOADINGS (LBS PER WHEEL PAIR):				
FULL UP		FULL DOWN		
LEFT SIDE	RIGHT SIDE	LEFT SIDE	RIGHT SIDE	
567	891	829	761	
HOOKBLOCK DRIFT AT FULL DOWN POSITION (IN.) (X): 3-3/4				
HOIST NOTES:				
1. LARGER CONTROL BOXES MAY NEED TO BE RELOCATED				
2. NO TRACKS SMALLER THAN S6				
3. TRACK WIDTH EXCEEDS 5" = 20-7/8"				



ELECTROLIFT, INC.  
204 SARGEANT AVE.  
CLIFTON, NJ 07013  
PH: 973-471-0204  
FAX: 973-471-2814  
www.electrolift.com

REV.	ECO#	DATE	BY:	
HOIST TYPE: "A" SINGLE HOOK				
CONFIGURATION: SIDE DRIVE TROLLEY				
DATE: 7/13/04	SCALE: 1:12	DWG SIZE: B	DRAWN BY: AR	
CATALOG NO.: 22-SD		DRAWING NO.: A-115		