



SPECIFICATIONS:

- 1. WIRE ROPE:**
FOR USE WITH 1/4" OR 5/16" DIAMETER WIRE ROPE
- 2. PITCH DIAMETER**
4" P.D.
- 3. MATERIAL:**
CAST IRON
- 4. BEARING:**
ROLLER BEARING
SUITABLE FOR HEAVY DUTY APPLICATION
- 5. BEARING LIFE:**
STATIC LOAD RATING:
14,100 LBS.

BASIC DYNAMIC LOAD RATING:
5450 LBS.

AT 33-1/3 RPM FOR
500 HRS MIN (L10) LIFE
- 6. SHAFT BORE DIAMETER:**
7/8"
- 7. SHAFT DIAMETER REQUIRED:**
+.0000
.8750" - .0010
- 8. SHAFT HARDNESS:**
CASE HARDENED TO 60 R.C.
- 9. SHAFT SURFACE FINISH REQUIRED:**
8 ✓ MAX.



ELECTROLIFT, INC.
204 SARGEANT AVE.
CLIFTON, NJ 07013
PH: 973-471-0204
FAX: 973-471-2814
www.electrolift.com

-	ECO#	DATE	BY:
SHEAVE PART NUMBER: K103P3			
DATE: 2/27/08	SCALE: 1/2	DWG SIZE: A	DRAWN BY: DR

DRAWING NO:
K103P3-WPDF