

SPECIFICATIONS:

1. WIRE ROPE:

FOR USE WITH 9/16" DIAMETER
WIRE ROPE

2. PITCH DIAMETER

10" P.D.

3. MATERIAL:

CAST IRON

4. BEARING:

ROLLER BEARING
SUITABLE FOR HEAVY
DUTY APPLICATION

5. BEARING LIFE:

STATIC LOAD RATING:
46,000 LBS.

BASIC DYNAMIC LOAD RATING:
10,920 LBS.

AT 33-1/3 RPM FOR
500 HRS MIN (L10) LIFE

6. SHAFT BORE DIAMETER:

2"

7. SHAFT DIAMETER REQUIRED:


2.0000"
+0.0000
-0.0010

8. SHAFT HARDNESS:

CASE HARDENED TO 60 R.C.

9. SHAFT SURFACE FINISH REQUIRED:

8 ✓ MAX.



ELECTROLIFT, INC.
204 SARGEANT AVE.
CLIFTON, NJ 07013
PH: 973-471-0204
FAX: 973-471-2814
www.electrolift.com

REV.	ECO#	DATE	BY:
SHEAVE PART NUMBER: M1210P4AS			
DATE: 2/27/08	SCALE: 1/3	DWG SIZE: A	DRAWN BY: DR

DRAWING NO:
M1210P4AS-WPDF